



Installation Information (coaxial only)

MODEL	OVERALL DIMENSIONS			WATER CONN.	REF. CONN.	OTHER DIMENSIONS					APPROX. DRY WEIGHT
	A	B	H	Di + Do	di + do	a	h	S	L	W	(Kg)
CK1-3	250	290	80	15.9	12.7	225	55	22	130	70	3
CK2-5	235	290	120	15.9	15.9	210	100	22	130	70	5
CK3-10	315	350	170	19.1	15.9	290	145	25	150	100	10
CK6-13	330	380	290	22.2	22.2	295	265	35	150	100	21
CK8-20	400	460	320	25.4	22.2	360	285	38	170	100	30
CK15-30	540	600	250	38.1	28.6	480	195	54	250	100	40
CK25-50	530	630	390	38.1	28.6	470	362	62	250	100	80

Insulation Details

MODEL	X	Y	Z
CK1-3	275	275	105
CK2-5	275	275	145
CK3-10	355	355	195
CK6-13	385	385	315
CK8-20	500	500	345
CK15-30	575	575	275
CK25-50	725	725	355

*NOTE - Refrigeration terminations either (A) or (B), as specified

Dimensions given are approximate and are for guidance only
Prices are available upon request

BEEHIVE COILS LTD
 STUDLANDS PARK AVENUE, NEWMARKET, SUFFOLK CB8 7AU
 Tel: +44 (0)1638 664134 Fax: +44 (0)1638 561542
 Email: info@beehivecoils.co.uk www.beehivecoils.co.uk

THIS DRAWING AND DESCRIPTIVE MATTER ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF BEEHIVE COILS LTD. THIS DRAWING IS NOT TO BE COMMUNICATED, DISCLOSED, COPIED OR PUBLISHED WITHOUT AUTHORISATION IN WRITING BY BEEHIVE COILS LTD

TOLERANCES
 UNLESS STATED OTHERWISE

1	± 1.0mm
1.0	± 0.5mm
1.00	± 0.25mm
1.000	± 0.05mm
Angular	± 2°

1st ANGLE

CUSTOMER: **BEEHIVE COILS**

CUST REF/DWG:

DESCRIPTION: **COAXIAL CONDENSERS
STANDARD RANGE
(Insulated)**

DRWN: RB
 DATE: 31/08/06
 PED: VAR
 AUTH: MB

REV	E.C.N.	DATE	AUTH

CUST APPR:

BC 2000/COAX(INS)